

Effective October 3, 2015, revised May 16, 2016

## SAFETY DATA SHEET

Globally Harmonized System of Classification and Labeling of  
Chemicals (GHS)

PRO CUT POLISH

### 1. Substance/Preparation And Company Identification

**Name of the Product:** Perfect Cut Polish

**Other Means of Identification:** Rubbing Compound

**Recommended use:** Polishing automotive finishes.

**Supplier Information:**

**Company:** System 51

633 S. Melrose Street

Placentia, CA 92870

**Company Phone Number:** 714-660-2796

**Emergency Phone Number:** 909-260-4263

### 2. Hazards Identification

#### GHS Classifications

Hazard	Category	Signal Word	Hazard statement	Symbol
<b>Physical Hazards</b>	None, not flammable	None	None	None
<b>Health Hazards Acute Toxicity</b>	5	Warning	H303, May be harmful if swallowed	None
<b>Skin Corrosion /Irritation</b>	5	Warning	H313, May be harmful in contact with skin.	None
<b>Eye Irritation</b>	2B	Warning	H320, Causes Eye irritation	None
<b>Aspiration Hazard</b>	2	Warning	H305, May be harmful if swallowed and enters airways	Health Hazard

**Emergency Overview:**

Warning! Contains petroleum distillates that can cause chemical pneumonia if aspirated into the lungs as a liquid. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Eye and skin contact will result in irritation.

**Route of Entry:** Inhalation: yes. Skin: yes. Ingestion: yes.

**Carcinogenicity:** NTP: no. IARC: no. OSHA: no.

**Reproductive Toxicity:** Not a reproductive toxicant.

**Specific Target Organ Systemic Toxicity (TOST):** Single Exposure: Irritating to the skin and eyes and respiratory tract. Prolonged exposure will affect the nervous system, causing nervous system depression.

**Effects of Exposure:**

**Acute:** Eye: Category 2B. Mild irritant, Reversible in 7 days. Irritation, redness, tearing and blurred vision.

**Skin:** Category 5. Mild Skin Irritation. Reversible adverse effects in dermal tissue.

**Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. High concentrations may result in narcosis (central nervous system depression). Intentional inhalation in concentrated form (huffing) may lead to brain damage and death.

**Ingestion:** Can cause gastrointestinal irritation, nausea, vomiting and effects of overexposure.

**Signs and Symptoms of Overexposure:**

**Health hazard:** diarrhea. Aspiration of material into lungs can cause chemical pneumonia which can be fatal.

**Medical Conditions Aggravated by Exposure:** Asthma.

**LABELING:**

Product identifier: Perfect Cut Polish

Signal word: Warning

Hazard statements: H303, May be harmful if swallowed. H313, May be harmful in contact with skin. H320, Causes Eye irritation. H305, May be harmful if swallowed and enters airways

Causes Skin and Eye Irritation. Do not breathe vapors or mist. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

#### FIRST AID

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**SKIN:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops and persists.

**COMPANY NAME:** System 51  
**ADDRESS:** 633 S. Melrose Street  
Placentia, CA 92870

**Phone number:** 714-660-2796

**HAZARDS:** (Liquid) Mild skin and eye irritant.

#### **Pictograms on the label:**



**Warning:** May cause damage to central nervous system through prolonged or repeated inhalation.

**Warning: Aspiration Hazard:** May be harmful if swallowed and enters airways

**Warning:** May cause respiratory irritation when inhaled.

#### Hazard Statements

H303	May be harmful if swallowed
H305	May be harmful if swallowed and enters airways.
H313	May be harmful in contact with skin.
H320	Causes eye irritation
H335	May cause respiratory irritation

## Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray  
 P305 +P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. If present and easy to do. Continue rinsing.

### 3. Composition/Information On Hazardous Ingredients

Hazardous Ingredient	w/w%	CAS No	OSHA PEL ppm
Aliphatic Hydrocarbon	5-50	6472-48-9	171
Mineral Oil	5-50	8042-47-5	NE*
Aminofunctional additive	5-50	237753-63-8	NE
Aluminum Oxide	5-50	1344-28-1	5mg/m <sup>3</sup>

\*Note: NE=Not Established

Note: Further safety information can be found in subsequent sections.

### 4. First aid measures

**General Information:** Discard contaminated clothing immediately.

**Eye:** Flush with clean, lukewarm water for at least 15 minutes, occasionally lifting eyelids.

Obtain medical attention.

**Skin:** Remove contaminated clothing. Wash affected skin areas thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse.

**Inhalation:** Remove to fresh air. Apply artificial respiration/administer oxygen if necessary. Call physician immediately. If person is unconscious, transport affected person in reclined position.

**Ingestion:** Keep person warm and quiet. Get immediate medical attention. Do not induce vomiting because of risk of aspiration of material into lungs. Drink several glasses of water to dilute the product in the stomach.

## 5. Fire Fighting Measures

Flammability Summary (OSHA): Not Flammable

Flash Point Method: Setaflash

Flash Point: Greater than 200F (93C)

Upper Flammable/Explosive Limit, % in air: Not Found

Lower Flammable/Explosive Limit, % in air: Not Found

When dry:

Upper Flammable /explosive limit, % in air: NA

Lower Flammable / explosive limit, % in air: NA

Unusual Fire/Explosion Hazards: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to fire.

**Extinguishing Media:** Use water fog, foam, carbon dioxide or chemical fire fighting apparatus.

**Fire Fighting Instructions:** Wear NIOSH/MSHA approved SCBA and full protective equipment. Do not use full pressure water jet. Water spray may be used for cooling containers to prevent possible pressure build up and auto ignition/explosion when exposed. Guard against toxic gasses released by fire. If safe, remove containers from fire zone.

Products of Combustion: Carbon Dioxide, Carbon Monoxide, Water Vapor.

## 6. Accidental Release Measures

Slip and fall hazard. Evacuate the area of all unnecessary personnel..

Ventilate area. Equip employees with appropriate protective equipment.

Dike around spilled material. Cover spill with inert/absorbent material and shovel into container. Remove containers to safe area and seal. Use sand or absorbent to collect material and to prevent flow into storm water or ground.

Waste Disposal Methods: Waste material must be disposed of in accordance with federal, state and local environmental regulatory controls.

## 7. Handling And Storage

Handling:

Drums: Protect against physical damage.

Bulk: Storage should be in standard lidded storage tanks.

Other Precautions: Clean up spills quickly to prevent slipping on the wet surface.

## 8. Exposure Controls and Personal Protection

### **Respiratory Protection:**

Use NIOSH/MSHA approved self-contained breathing apparatus where vapor concentration may be above TLV limits. Below TLV limits use NIOSH/MSHA approved vapor respirator or an airline respirator with escape bottle provisions.

### **Ventilation:**

Local exhaust must be sufficient to keep airborne vapor concentrations below TLV limit. Exhaust air may need to be cleaned by scrubbers.

**Protective Gloves:** Chemical resistant gloves.

**Eye Protection:** Chemical workers' goggles.

### **Other Protective Equipment:**

**Eye bath and safety shower.** To prevent repeated or prolonged skin contact wear impervious clothing and boots.

**Work Hygiene Practices:** Wash hands and clothing after exposure.

**Supplemental Safety and Health:** First aid procedures: Vomit can cause chemical pneumonia which can be fatal.

**Ventilation:** Filters to reduce environmental contamination.

**Effects of overexposure:** Irritating to respiratory system. Mild, reversible liver effects, liver abnormalities.

### **Exposure Limits:**

Hazardous Ingredient	w/w%	CAS No	OSHA PEL ppm
Aliphatic Hydrocarbon	5-50	6472-48-9	171
Mineral Oil	5-50	8042-47-5	NE*
Aminofunctional additive	5-50	237753-63-8	NE
Aluminum Oxide	5-50	1344-28-1	5mg/m <sup>3</sup>

NE=Not Established

## 9. Physical and Chemical Properties

**Physical State:** Liquid

**Color:** milky when liquid, clear when dry and solid

**Odor:** slight

**Odor Threshold:** not available.

**pH Value:** 7

**Melting point:** Not available

**Evaporation rate:** Slower than ether

**Freezing point:** Not available.

**Initial boiling point:** 100C (212F)

**Auto ignition Temperature:** 395C(743F)

**Bulk Density:** Approximately 8.25 pounds per gallon.

**Flash Point:** >200F PMCC

**Upper Explosion Limit:** Not established

**Lower Explosion Limit:** Not established

**Solubility in Water:** miscible.

**Specific Gravity:** 0.99@20C(68F)

**VOC:** 15%v/v. 3.2 pounds per gallon less water.

### 10. Stability and Reactivity

**Stability and Reactivity Summary:** Stable under normal conditions

**Reactive Properties:**

**Sensitivity to mechanical shock:** None

**Hazardous Polymerization:** Will not occur

**Conditions to Avoid:** Do not heat closed containers

**Chemical Incompatibility:** Strong oxidizing agents

**Hazardous Decomposition Products:** CO, CO2

### 11. Toxicological Information

Hazardous Ingredient	w/w%	CAS No	LD50 Oral Rat mg/kg	LD50 Dermal mg/kg
Aliphatic Hydrocarbon	5-50	6472-48-9	10,000	1360
Mineral Oil	5-50	8042-47-5	50,000	>2000
Aminofunctional additive	5-50	237753-63-8	NF	NF
Aluminum Oxide	5-50	1344-28-1	>5000	NF

\*NF=Not Found

### 12. Ecological Information

**Environmental Toxicity:** Not persistent in the environment. Ecotoxicity

Classification criteria is between 1 and 100 for some of the ingredients.

Most ingredients are carbon based and are eventually degraded by bacteria when placed in water or soil.

### 13. Disposal Considerations

Care must be taken to avoid environmental contamination from the use of this material. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws.

**Waste Disposal Summary:** Dispose as a hazardous chemical.

**Disposal Methods:**

Dispose of in accordance with local, state and federal regulations. Incineration is preferred.

#### 14. Transport Information

**US Ground (DOT):** Not regulated for transportation.

**Canada (TDG):** Not regulated for transportation.

**IMO:** Not regulated for transportation.

**IATA/ICAO:** Not regulated for transportation.

#### 15. Regulatory Information

UNITED STATES:

**Toxic Substances Control Act (TSCA):** The components of this product are listed on the TSCA Inventory of Existing Chemical Substances.

**Superfund Amendments and Reauthorization Act (SARA) Title III: Sections 311/312 Hazard Categories (40 CFR 370.2):**

**Immediate/Acute Health Hazard:** Yes

**Delayed/Chronic Health Hazard:** Yes

**Fire Hazard:** No

**Pressure Hazard:** No

**Reactivity Hazard:** No

**Federal and State Regulations:**

California Prop 65: No materials are present that are listed on the Prop 65 list of cancer causing chemicals or birth defect or reproductive harm causing chemicals.

SARA 313 toxic chemical notification and release reporting: None

CERCLA Reportable Quantities: None

HMIS (U.S.A.):

Health Hazard: 1

Fire Hazard: 0

Reactivity: 0

Personal Protection: A

National Fire Protection Association (U.S.A.):

Health: 1



Flammability: 0

Reactivity: 0

### 16. Other Information

This information should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. While the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to its use. No warranties of any kind neither express nor implied, including warranties of merchantability or fitness for a particular purpose are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, information, data and designs furnished by SYSTEM 51 hereunder are given gratis and SYSTEM 51 assumes no obligation or liability for the description, information, data and designs given or results obtained, all such being given and accepted at your risk. We believe this information to be reliable and up to date as of its publication date, but make no warranty that it is. If this SDS is more than one year old you should contact SYSTEM 51 to make sure the information is still current.

Prepared by V.C. Bud Jenkins, BS, MBA, JD, CHMM, CHWP  
Coatings Scientist Consulting Services, [www.coatingsscience.com](http://www.coatingsscience.com)